



**Baureihe 173 Standardzylinder einfachwirkend ohne Befestigung**

| 180 bar - Reihe |             | Maße in mm |     |    |    | Temperatur °C -30 / +110 |    | Druckkraft<br>daN / 180 bar |
|-----------------|-------------|------------|-----|----|----|--------------------------|----|-----------------------------|
| Baureihe        | Stange<br>Ø | R<br>Ø     | A   | A1 | U  | G                        | F  |                             |
| 173             | Ø           | Ø          |     |    |    |                          |    |                             |
| E-30-Hub        | 30          | 46         | 90  | 65 | 25 | G3/8                     | 25 | 1272                        |
| E-38-Hub        | 38          | 55         | 90  | 65 | 25 | G3/8                     | 25 | 2041                        |
| E-45-Hub        | 45          | 62         | 95  | 70 | 25 | G3/8                     | 25 | 2862                        |
| E-50-Hub        | 50          | 66         | 102 | 77 | 25 | G3/8                     | 25 | 3534                        |
| E-60-Hub        | 60          | 76         | 115 | 90 | 25 | G1/2                     | 30 | 5089                        |
| E-70-Hub        | 70          | 90         | 115 | 90 | 25 | G1/2                     | 30 | 6927                        |
| E-80-Hub        | 80          | 100        | 115 | 90 | 25 | G1/2                     | 30 | 9047                        |
| E-100-Hub       | 100         | 120        | 115 | 90 | 25 | G1/2                     | 30 | 14137                       |

Bestellung: Baureihe 173 Stange Ø38 Hub 100

Stange hartverchromt Chromschicht 25 µm

Hublänge frei wählbar

Bestellnummer **173 / E - 38 - 100 - 190**